

**TQSDT**

208~230V 2-Way Cassette

Model:TVRF-IE2WC09KHP



Specifications	Unit	Parameter
Model	—	TVRF-IE2WC09KHP
Performance		
Rated Cooling Capacity	kBtu/h	9.5
Rated Heating Capacity	kBtu/h	10.5
Sound Pressure Level	dB(A)	31/33/35
Electrical Data		
Power Supply	Voltage,Phase, Hertz	208/230,1,60
Maximum Overcurrent Protection (MOP)	A	15
Minimum Circuit Amps (MCA)	A	1
Fan		
Type x Quantity	—	Centrifugal×3
Air Flow Volume	CFM	312/355/490
Fan Motor Running Current	A	0.6
Fan Motor Power Output	W	90
Refrigerant Piping		
Connection Pipe	Gas(mm/inch)	Φ9.52/Φ3/8
	Liquid(mm/inch)	Φ6.35/Φ1/4
Connection method	—	Flare Connection
Refrigerant	—	R410A
Dimension/Weight		
Dimensions (H×W×D)	mm/inch	315×1200×520 (12-3/8×47-1/4×20-1/2)
Net Weight	kg/lbs	43/95
Other		
Safety Certification	—	ETL

Job Name:

Date:


System Reference No.:

Engineer Signature:


Specifications subject to change without prior notice.

Outline and Physical Dimensions of TVRF-IE2WC09KHP.

Main Body



TE01 panel



Unit:mm(in.)