

208~230V 2-Way Cassette

Model:TVRF-IE2WC24KHP





Specifications	Unit	Parameter
Model	—	TVRF-IE2WC24KHP
Performance		
Rated Cooling Capacity	kBtu/h	24
Rated Heating Capacity	kBtu/h	27
Sound Pressure Level	dB(A)	35/37/39
Electrical Data		
Power Supply	Voltage,Phase, Hertz	208/230,1,60
Maximum Overcurrent Protection (MOP)	A	15
Minimum Circuit Amps (MCA)	A	1
Fan		
Type x Quantity	—	Centrifugal×3
Air Flow Volume	CFM	448/483/650
Fan Motor Running Current	A	0.7
Fan Motor Power Output	W	90
Refrigerant Piping		
Connection Pipe	Gas(mm/inch)	Φ15.9/Φ5/8
	Liquid(mm/inch)	Φ9.52/Φ3/8
Connection method	—	Flare Connection
Refrigerant	—	R410A
Dimension/Weight		
Dimensions (H×W×D)	mm/inch	315×1200×520 (12-3/8×47-1/4×20-1/2)
Net Weight	kg/lbs	46/101
Other		
Safety Certification	—	ETL

Job Name:		Date:	
System Reference No.:			
Engineer Signature:			

Specifications subject to change without prior notice.

Outline and Physical Dimensions of TVRF-IE2WC24KHP.



Unit:mm(in.)