

Multi zone inverter mini split**TOSOT****MODEL: TM12HEDI**

Project Name:

Engineer Name:

Unit Designation:

Submitted To:

Date:

Location:

Purchaser:

Schedule No.

General Features

- 2 Thermistor control
- 24-Hour on/off Timer
- Auto operation
- Auto restart
- Chaos swing
- Control lock function



- High And Low Pressure Protection Features
- Load Protection Features
- Over-Current Protection
- Anti Freeze Protection
- Wireless Remote control
- Optional Wired controller

Unit Performance:

Nominal Cooling Capacity (Btu/h)	12,000
Nominal Heating Capacity (Btu/h)	13,000

Set Temperature

Cooling (°F)	61~86
Heating (°F)	61~86

Piping

Liquid Line (in, OD)	1/4
Gas Line (in, OD)	3/8
Drain OD (in)	1.1

Electrical Specification

Power Supply	208-230V / 60Hz
Communications Wire Size	AWG 14/4
Rated Amps (A)	0.14

Fan

Type	Centrifugal
Quantity	1
Motor/Drive	Direct Drive
Air Flow Rate (CFM)	441/382/353/324/294/265/206

Unit Specification

Refrigerant Type	R410A
Refrigerant Control	EEV
Sound Pressure (dB(A))	43/40/38/37/35/32/27
Primary Filter	Yes
Net Weight (lbs)	33
Dehumidification (Pt/h)	2.95

**GLOSSARY**

SEER - Seasonal Energy Efficiency Ratio

EER - Energy Efficiency Ratio

HSPF - Heating Seasonal Performance Factor

MOP - Maximum Overcurrent Protection


MCA - Minimum Circuit Ampacity

Multi zone inverter mini split

TOSOT

MODEL: TM12HEDI

Outline Dimension Diagram



mm	Inch
700	27.5
600	23.6
215	8.4
205	8
398	15.6
22	0.8

Approved By:

Signature

Date

TOSOT

315 Boulevard Industriel, Châteauguay, QC, Canada J6J 4Z2
Contact: +1 (450) 698-4000
info@tosotamerica.com
tosotamerica.com